

Leclanché Capacitors
48, av. de Grandson
1400 Yverdon, Switzerland



Tel. +41 24 445 66 88
Fax +41 24 445 66 89
capinfo@Lcap.ch
www.Lcap.ch

Drawing No. : 1026731-53154
created from : 14/02/2014 15:14:00

Part Number : SI4P33236035125

| | | |
|--|--|---|
| | <p>∅ D : 35 mm L : 125 mm h : 4,5 mm</p> | <p>Drill plan</p> |
| <p>Insulation : PVC 2500 Vac Terminals : Snap In</p> | | <p>NC terminals could be connected to the electrical circuit!</p> |

Electrical Parameter

| | | |
|--|----------------------|--------------------|
| Rated Capacitance (C_R) @ 100 Hz / 20 °C | 3300 μ F | |
| Tolerance | ±10 % | |
| Rated Voltage (U_R) | 360 V | |
| Surge Voltage (U_S) max. 5 x 1 min / h | 375 V | |
| Reverse Voltage (U_U) max. 1 s | 2 V | |
| Leakage Current (I_L) @ U_R / 5 min / 20 °C | 7128 μ A | |
| ESR typ. @ 100 Hz / 20°C | 29 m Ω | |
| Tan δ typ. @ 100 Hz / 20°C | 6 % | |
| Z max. @ 10 kHz / 20°C | 23 m Ω | |
| ESL typ. | 20 nH | |
| No of flashes | 10 Mio h | |
| IEC Climatic category / Standards | 40/60/56 | IEC 60384-4 |
| Applications | Flash | |
| Your article No. / Project | | |