

Leclanché Capacitors
48, av. de Grandson
1400 Yverdon, Switzerland



Tel. +41 24 445 66 88
Fax +41 24 445 66 89
capinfo@Lcap.ch
www.Lcap.ch

Drawing No. : Preliminary ...1026115
created from : 09/07/2014 16:03:00

Part Number : Cuboid Cap CC22206316035035

	<p>l : 35 mm B : 16 mm H : 35 mm a : 10 mm : Terminals : Wire 0,8mm</p>	<p>Sealing Laser welded Al with Teflon gaskets</p>
--	---	--

Electrical Parameter

Rated Capacitance (C_R) @ 100 Hz / 20 °C	2200 μ F	
Tolerance	±20 %	
Rated Voltage (U_R)	63 V	
Surge Voltage (U_S) max. 5 x 1 min / h	72 V	
Reverse Voltage (U_U) max. 1 s	2 V	
Leakage Current (I_L) @ U_R / 5 min / 20 °C	830 μ A	
ESR typ. @ 100 Hz / 20°C	72 m Ω	TBD in Measurement
Tan δ typ. @ 100 Hz / 20°C	10 %	TBD in Measurement
Z max. @ 10 kHz / 20°C	58 m Ω	TBD in Measurement
ESL typ.	20 nH	
Rated Ripple Current (I_R) @ 100 Hz / 125 °C	2 A	TBD in Measurement
Useful life @ I_R , U_R , 125 °C	10000 h	
IEC Climatic category / Standards	40/125/56	IEC 60384-4 Storage at -55°C possible
Applications	Military	
Your article No. / Project		