


#6123

HIGH VOLTAGE METALLIZED CAPACITORS

PPMHT 400-022 daS K



Dielectric of metallized polypropylene

Polyester wrapped / Epoxy resin sealing

| Parameter | Symbol | Value | Unit | Condition |
|----------------------------------|-------------|----------------|------------------|-----------------|
| Capacitance | C | 220 | nF | 1 V / 1 kHz |
| Tolerance | | ± 10 | % | |
| Rated voltage | Un DC | 4'000 | VDC | |
| Rated voltage | Un AC | 750 | Veff | 50 Hz |
| slope of voltage variation | du/dt max. | 275 | V/ μ sec | max. repetitive |
| RMS current | I RMS max. | 3.50 | Aeff | 10 kHz |
| Tangent delta | tg δ | < 4 | 10 ⁻⁴ | 1 V / 1 kHz |
| Tangent delta | tg δ | < 6.5 | 10 ⁻⁴ | 1 V / 10 kHz |
| Stray inductance | ESL | ≤ 50 | nH | |
| Insulation resistance | Ri | >100'000 | M Ω | 500 VDC - 1 min |
| Test voltage between terminals | U T1 | 6'400 | VDC | 10 s |
| Operating temp. | | - 40 / + 85 °C | | |
| Estimated operational life (-3%) | | 100'000 | h | Un DC / 70°C |

| Dimension | Symbol | Value | Unit | Conditions |
|-------------------|--------------|---------------|---------------|------------|
| Diameter | D | 23.5 | mm | |
| Length | L | 48 | mm | |
| Terminals | | | | |
| Axial tinned wire | d | 1 | mm | |
| | RM | 55 \pm 0.7 | mm | |
| | i | 4.5 \pm 0.5 | mm | |
| | M1 | | | |
| | M0 | | | |
| | Modification | Date | Visa émetteur | |

Condensateurs CH 1400 Yverdon, Switzerland
 Kondensatoren Tel.: ++41 24 445 66 88
 Capacitors Fax: ++41 24 445 66 89

Lecranché
Capacitors
A FISOCHNER & TEUSCHKE COMPANY

HJJ

www.Lcap.ch
 28.08.2012

capinfo@Lcap.ch
 faisab6123.XLS