



Power Link

Features

- High CV product
- Compact design
- Overvoltage capability

Applications

- High-end and industrial power supplies
- Solar inverters
- Frequency converters

Other voltage and capacitance combinations available on request.

General specifications

Items	Characteristics
Capacitance Range	6 ... 65 μ F
Rated Voltage DC	From 700VDC to 1500 VDC
Available Tolerance	\pm 5% (J) or \pm 10% (K)
Rated RMS Current @ 30 °C	max. 29 A
Operating Temperature Range	-40 °C ... + 85 °C
Climatic Category DIN IEC 68/1	40/085/21
Terminals	PCB Pins 4x 1 mm or 4x 1,2 mm
Capacitance Range	From 6 μ F to 65 μ F

Electrical data and part numbers :

Un	Cn	Dimensions	Pitch	Max ESR @ 10kHz	dU/dt	Max. I _{rms} @ 10kHz/30°C	I _{peak}	Energy	R _{th}	Weight (approx)	Part Number
[Vdc]	[μF]	[mm]	[mm]	[mOhm]	[V/μs]	[A]	[A]	[Ws]	[K/W]	[g]	
700	24	40x27x36	37,5x16	9	33	22	795	5,9	14	50	PL24μ700d040027036...
	33	43x30x45	37,5x16	7	33	29	1093	8,1	11	75	PL33μ700d043030045...
	50	58x30x45	52,5x20,3	9	22	28	1116	12,3	9	100	PL50μ700d058030045...
	65	58x35x50	52,5x20,3	7	22	29	1451	15,9	7	135	PL65μ700d058035050...
900	16	40x27x36	37,5x16	10	41	20	662	6,5	14	50	PL16μ900d040027036...
	22	43x30x45	37,5x16	6	41	29	911	8,9	11	75	PL22μ900d043030045...
	32	58x30x45	52,5x20,3	11	28	26	893	13,0	9	100	PL32μ900d058030045...
	42	58x35x50	52,5x20,3	8	28	29	1172	17,0	7	135	PL42μ900d058035050...
1100	11	40x27x36	37,5x16	13	50	18	303	6,1	14	50	PL11μ1100d040027036...
	15	43x30x45	37,5x16	9	50	24	745	9,1	11	75	PL15μ1100d043030045...
	22	58x30x45	52,5x20,3	13	33	23	737	13,3	9	100	PL22μ1100d058030045...
	30	58x35x50	52,5x20,3	10	33	29	1004	18,2	7	135	PL30μ1100d058035050...
1300	8	40x27x36	37,5x16	15	58	17	464	6,8	14	50	PL8μ1300d040027036...
	10	43x30x45	37,5x16	12	58	22	580	8,5	11	75	PL10μ1300d043030045...
	16	58x30x45	52,5x20,3	15	39	22	625	13,5	9	100	PL16μ1300d058030045...
	21	58x35x50	52,5x20,3	12	39	27	820	17,8	7	135	PL21μ1300d058035050...
1500	6	40x27x36	37,5x16	16	66	16	397	6,8	14	50	PL6μ1500d040027036...
	8	43x30x45	37,5x16	13	66	21	530	9,0	11	75	PL8μ1500d043030045...
	12	58x30x45	52,5x20,3	17	45	20	536	13,5	9	100	PL12μ1500d058030045...
	16	58x35x50	52,5x20,3	13	45	25	714	18,0	7	135	PL16μ1500d058035050...

Mechanical drawing :

