

**Application:** MKP-AC capacitor for general use in power electronics also for nonsinusoidal voltages and currents with low self inductance

**Standard:** acc. to IEC 61071:2007

### Characteristics

Rated capacitance	$C_N$	1500 $\mu\text{F} \pm 10\%$
Rated d.c. voltage	$U_N$	900 V d.c.
Ripple voltage	$U_r$	640 V
Insulation voltage	$U_i$	1000 V
Non-recurrent surge voltage	$u_s$	1800 V
Rated energy	$W_N$	600 Ws
Maximum current	$I_{\max}$	410 A
Maximum peak current	$\hat{I}$	15 kA
Maximum surge current	$I_s$	150 kA
Series resistance	$R_s$	0.12 m $\Omega$
Dielectric loss factor	$\tan\delta_0$	$2 \times 10^{-4}$
Loss factor at 50Hz	$\tan\delta_{50\text{Hz}}$	$2.6 \times 10^{-4}$
Self discharge time const.	$C \times R_{is}$	10000 s
Self inductance	$L_e$	60 nH
Resonance frequency	$f_r$	17 kHz

### Thermal conditions

Lowest operating temperature	$\Theta_{\min}$	-25 °C
Maximum operating temperature	$\Theta_{\max}$	75 °C
Thermal resistance	$R_{th}$	0.4 K/W <sup>1)</sup>
Maximum power loss	$P_{\max}$ <sup>1)</sup>	at $\Theta_{\text{amb}}$
	77 W	45 °C
	64 W	50 °C
	38 W	60 °C
	13 W	70 °C
Storage temperature	$\Theta_{\text{storage}}$	-40..+85 °C
Humidity class		C

### Service life

Load duration	100000 h
at $\Theta_{\text{hotspot}}$	≤ 70 °C
Failure quota	300 FIT

### Test data

Voltage test between terminals	$U_{BB}$	1935 V DC/10s
A.C. voltage test terminal/contai	$U_{BG}$	3000 V AC/10s

### Dimensions<sup>2)</sup>

Height of the case	$H$	550 mm
Lenght of the case	$L$	340 mm
Width of the case	$W$	125 mm
Distance of terminals	$a$	80 mm
Clearance in air	$L$	26 mm
Creepage distance	$K$	48 mm

**Approx weight** 31 kg

### Mechanical characteristics

Construction	MKP-AC - metallized polypropylene capacitor, self-healing,metallic case	
Protection	pressure switch for monitoring of the internal pressure (opener)	
Impregnant	dry type ,resin moulded (Non PCB)	
Fire load	630MJ	

1) exact values have to be determined at the type test

### outline drawing

