

Leclanché Capacitors
48, av. de Grandson
1400 Yverdon, Switzerland




Tel. +41 24 445 66 88
Fax +41 24 445 66 89
capinfo@Lcap.ch
www.Lcap.ch

Drawing No. : 1023171-53567

created from : 05/06/2012 12:55:00

Part Number : GMA47306365105



∅ D : 65 mm
L : 105 mm
a : 28,5 mm
h : 4 mm

Terminals : M5

Electrical Parameter

Rated Capacitance (C_R) @ 100 Hz / 20 °C	47000 μF	
Tolerance	±20 %	
Rated Voltage (U_R)	63 V	
Surge Voltage (U_S) max. 5 x 1 min / h	72 V	
Reverse Voltage (U_U) max. 1 s	2 V	
Leakage Current (I_L) @ U_R / 5 min / 20 °C	35 mA	
ESR typ. @ 100 Hz / 20°C	6 mΩ	
Tan δ typ. @ 100 Hz / 20°C	18 %	
Z max. @ 10 kHz / 20°C	5 mΩ	
ESL typ.	20 nH	
Rated Ripple Current (I_R) @ 100 Hz / 105 °C	17 A	
Useful life @ I_R , U_R , 105 °C	8000 h	
IEC Climatic category / Standards	40/105/56	IEC 60384-4
Applications	General Industry	
Your article No. / Project		