

Leclanché Capacitors
48, av. de Grandson
1400 Yverdon, Switzerland



Tel. +41 24 445 66 88
Fax +41 24 445 66 89
capinfo@LCap.ch

Part No.
GMB12330575145

release: 18.02.2014 17:06:00

	<p> $\varnothing D$: 75 mm L : 145 mm a : 31,7 mm h : 5 mm B : M12 Terminals : M5 </p>	<p> Druck: <Leclanché Logo> Typ GMB 12000 μF 0% +30% 305 V 40/085/56 <Datecode> Farbe: schwarz </p>
Electrical Parameters		
Rated Capacitance (C_R) @ 100 Hz / 20 °C	12000 μ F	
Tolerance	-0 +30 %	
Rated Voltage (U_R)	305 V	
Surge Voltage (U_S) max. 5 x 1 min / h	350 V	
Reverse Voltage (U_U) max. 1 s	2 V	
Leakage Current (I_L) @ U_R / 5 min / 20 °C	21960 μ A	
ESR typ. @ 100 Hz / 20°C	9 m Ω	
Tan δ typ. @ 100 Hz / 20°C	7 %	
Z max. @ 10 kHz / 20°C	6 m Ω	
ESL typ.	20 nH	
Rated Ripple Current (I_R) @ 100 Hz / 85 °C	15 A	
Useful life @ I_R , U_R , 85 °C	8000 h	
IEC Climatic category / Standards	40/085/56	IEC 60384-4
Applications		
Your article No.. / Project		