

Ordering code:

PAM 68-40.0 cv2d

Applications:

AC/DC capacitor for general use in power electronics
also for nonsinusoidal voltages and currents

Standard:

acc. to IEC 61071:2007

Characteristics

Rated capacitance	C_N	40 $\mu\text{F} \pm 10\%$
Rated a.c. voltage	$U_{N\ AC}$	680 V a.c.
Rated d.c. voltage	$U_{N\ DC}$	1120 V d.c.
Max. rms voltage (sinusoidal)	U_{rms}	480 V
Non-recurrent surge voltage	U_s	1680 V
Rated energy	W_N	25.1 Ws
Maximum current	I_{max}	16 A
Maximum peak current	\hat{I}	0.4 kA
Maximum surge current	I_s	1.1 kA
Series resistance	R_s	8 m Ω
dielectric dissipation factor	$\tan\delta_o$	2×10^{-4}
insulation strength	$C \times R_{is}$	5000 s
Self inductance	L_e	120 nH

thermal characteristics

Lowest operating temperature	Θ_{min}	-25 °C
Maximum operating temperature	Θ_{max}	85 °C
storing temperature	$\Theta_{storage}$	-40..+85 °C
thermal resistance	R_{th}	6.9 K/W

test parameters

test voltage between terminals	U_{TT}	1680 V DC/10s
A.C. voltage test terminal/container	U_{TC}	3000 V AC/10s

failure rate

reference service life at $\Theta_{hotspot}$	100000 h
	$\leq 70^\circ\text{C}$

* See FIT-RATE diagram on pg.4

Dimensions

Rated diameter	D_1	45 (± 0.5) mm
Length of the case	L_1	143 (± 2.5) mm
Length of the terminals	L_2	12 (+3) mm
distance terminals	a	13.5 (± 1) mm
Terminal		DF 6.3 mm
base mounting stud	$G_B \times L_B$	M8x10 (+1) mm
Clearance in air	L	6.5 mm
Creepage distance	K	10 mm

Approx weight

0.3 kg

Mechanical characteristics

Dielectric	metallized polypropylene capacitor, selfhealing
Construction	aluminium can, plastic with rubber sealing, flanged can
Protection	overpressure disconnecter
Terminals	dual tab connectors 6.3 x 0.8 mm / plastic lid
Impregnant	liquid impregnants, no PCB
Fire load	12MJ

outline drawing
