


#5744

METALLIZED POLYPROPYLENE CAPACITORS

PPM 70-650.0 cv5 J



Dielectric of metallized polypropylene

Threaded outputs

Resin end sealing

Aluminium case

Parameter	Symbol	Value	Unit	Condition
Capacitance	C	650	μF	1 V / 1 kHz
Tolerance		± 5	%	
Rated voltage	Un DC	700	VAC	
Surge voltage	Us	1000	V cr.	
RMS Current permanent	I <sub>eff max.</sub>	35	A <sub>eff</sub>	
Repetitive surge courant	I cr. max	1400	A	
Tangent delta	tgδ	≤ 185	10 <sup>-4</sup>	1 V / 1 kHz
Equivalent serie resistance	ESR	25°C to 70°C	4.5	mΩ
Stray inductance	ESL		≤ 60	nH
Insulation resistance	Ri x C		≥ 30'000	s
Test voltage between terminals	U T1		1200	VDC
Test voltage terminals to case	U T2		2500	VAC
Climatic category			27/70/56	
Estimated operational life (-5 %)			> 160'000	h
Dimension	Symbol	Value	Unit	Conditions
Diameter	D	90	mm	
Height	H	145	mm	
Terminals				
Thread		M8 x 20	mm	
Thread spacing	e	45	mm	
Fixing stud		M12 x 16	mm	
Mass approx.	m	1	kg	
	M1			
	M0	25.08.2008	HJJ	
	Modification	Date	Visa émetteur	

Condensateurs CH 1400 Yverdon-les-Bains  
 Kondensatoren Tel.: ++41 24 447 22 82  
 Capacitors Fax: ++41 24 447 22 85

**Le Janché**  
**Capacitors**  
A FISCHER & FAUDSCHER COMPANY

HJJ

12.08.2008

faisab5744.XLS