


Leclanché Capacitors
 48, av. de Grandson
 1400 Yverdon, Switzerland



Tel. +41 24 445 66 88
 Fax +41 24 445 66 89
capinfo@Lcap.ch
www.Lcap.ch

Drawing No. : 1022764-53154
 created from : 30/01/2012 16:15:00

Part Number : AG22104012030



Ø D : 12 mm
 L : 30 mm
 l : 40 mm
 d : 0,8 mm

Terminals : Wire

Electrical Parameter

Rated Capacitance (C_R) @ 100 Hz / 20 °C	220 μ F	
Tolerance	-10 +30 %	
Rated Voltage (U_R)	40 V	
Surge Voltage (U_S) max. 5 x 1 min / h	46 V	
Reverse Voltage (U_U) max. 1 s	2 V	
Leakage Current (I_L) @ U_R / 5 min / 20 °C	52 μ A	
ESR typ. @ 100 Hz / 20°C	580 m Ω	
Tan δ typ. @ 100 Hz / 20°C	8 %	
Z max. @ 10 kHz / 20°C	495 m Ω	
ESL typ.	20 nH	
Rated Ripple Current (I_R) @ 100 Hz / 125 °C	0,4 A	
Useful life @ I_R , U_R , 125 °C	2000 h	
IEC Climatic category / Standards	55/125/56	IEC 60384-4
Applications	General Industrial	
Your article No. / Project		