



AEP 300

Bidirectional DC/AC converter

- Innovative in energy storage & Power Electronics
- Custom-made solutions
- Complete solution: storage & Power Electronics
- Design and system integration



Features

- 76 kW converter, U_n 400VAC
- Bidirectional half bridge 3-phase topology
- Load-dependent PWM fan control
- Low output current ripple for DC/DC application
- Short-circuit-proved output
- Integrated current and temperature sensors
- CAN-Bus communication

Applications

- Drive of AC- or DC-motors (including regenerative energy)
- Active filter
- Active Front End

Mechanical Data

Width x Depth x Height
502 x 477 x 203 mm
Approx. 22 kg

aephybridpower.com
sales@aephybridpower.com
+31 (0)78 692 2100



Technical Characteristics

Symbol	Parameter	Description	Value	Unit
General				
P_R	Rated power	@Uout 400VAC, $\cos(\phi)=1$	76	kW
P_{MAX}	Max. power	@Uout 400VAC, fr 2kHz 1min/10min	118	kW
F_r	Switching frequency		≤ 16	kHz
η_r	Efficiency	@ P_r	>95	%
Input				
U_{in}	Input voltage range		500-1100	VDC
$U_{in,max}$	Max. operating voltage		1200	VDC
Output				
U_{out}	Output voltage		400 - 690	VDC
f_N	Max. operating voltage		50/60	Hz
I_{nom}	Nominal phase current		110	A
I_{max}	Max. phase current	1 min / 10 min	170	A
Supply power				
	Control voltage	Rated Value between	24	VDC
			18 till 30	VDC
	Control current		2	A
Environment				
T_o	Operating temperature		0 till 50	°C
$T_{m,max}$	Advisable temperature		20 till 40	°C
T_s	Storage temperature		-20 till 60	°C
	Protection degree		IP20	
Cooling				
	Kind		Forced air cooling	
	Power losses		≤ 1500	W
	Airflow		600	m ³ /h
Communication				
	Data	CAN 2.0B / RS232		
	Binary signal	On/Off, Enable, Error, Reset, Emergency stop		
	Additionally	Conventional error, Temperature output		



Options

- IP20 & IP65
- Water cooling
- Profibus / Profinet
- Main contactor + Pre-charge

Mechanical Data

Width x Depth x Height: 502 x 477 x 203 mm
Weight converter: Approx. 22 kg
Enclosure: IP-20




Figure 1: Dimensions



Accessories




Figure 2: Mounting rails



Figure 3: Pre-charge



Figure 4: EMC filter



Figure 5: Voltage measurement




Figure 6: Output cap